

PLANNER, SELF-LEVELLING

ATTACHMENTS



LDR MEX TLS RTLS BHL



One Tough Animal.

PLANER, SELF-LEVELLING



REQUIREMENTS		PERFORMANCE*	FEATURES & BENEFITS
		Teeth life: 20 - 50 hours Drum life: 200 - 400 hours Production rate: 40 - 50 m ² /h	<ul style="list-style-type: none"> • Top access panel – for easier bit service and maintenance. • Self-levelling feature - for following irregular surfaces. • Hydraulic side-shift – for planing close to walls and curbs, and to easily reposition the drum for another pass. • Hydraulic depth adjustment on each ski - for constant contact to the ground, even working with one ski on the curb or on the surface already milled. • Hydraulic planer tilting – for planing sloping surfaces or to match two uneven surfaces. • Direct-drive high torque motors – for low maintenance and high efficiency. • Bob-Tach™ mounting system with quick-connect controls – for fast, easy attachment changes.
	Self-levelling Planer: For High Flow (H) machines only. Loader must be equipped with an Attachment Control Kit.	* Performances are estimated only and can vary depending on the type of concrete, depth of use, operator experience, ...	

Description: Equipped with direct-drive, high-torque hydraulic motor. These low maintenance attachments efficiently mill asphalt or concrete. Planers feature hydraulic side-shift, hydraulic independent ski depth control and hydraulic tilting. Self-levelling ski. Make precise adjustments with fingertip controls.

TECHNICAL SPECIFICATIONS

Description	Part Number	Maximum Cutting Width (cm)	Cutting Depth (with std drum) (cm)	Maximum Cutting Angle ± (°)	Sideshift (cm)	Minimum Planing Distance Next to Curb (cm)	Number of Bits	Weight (kg)	Control Kit Required	Working Flow	First Use Installation Time
Self-levelling Planer, 45 cm	7221391	45	15	15	65	6.5	42	742	Yes	High Flow	None
Self-levelling Planer 50 cm	7331126	50	17	15			42	845	Yes	High Flow	None
Self-levelling Planer, 60 cm	7221392	60	17	15	65	6.5	54	910	Yes	High Flow	None
Self-levelling Planer, 100 cm	6726632	102	13	8	65	6.5	78	1032	Yes	High Flow	None
Self-levelling Planer, 100 cm with 60 (fixed)/40 (removable) drum	1111142	100	13	8	65	6.5	54/32	1076	Yes	High Flow	None
Self-levelling Planer 120 cm	7331125	120	13	8	65		90	1135	Yes	High Flow	None

COMPATIBILITY CHARTS

Description		Part Number	Compact Track Loaders						Skid Steer Loaders and All-Wheel Steer Loaders												
			MT55	T450	T590/H	T650/H	T770/H	T870/H	S70	S100	S450	S510/H	S530/H	S550/H	S570/H	S590/H	S630/H	S650/H	S770/H	S850/H	A770/H
①	Self-levelling Planer, 45 cm	7221391			X	X						X	X	X	X	X	X				
	Self-levelling Planer 50 cm	7331126			X	X	X	X				X	X	X	X	X	X	X	X	X	
	Self-levelling Planer, 60 cm	7221392			X	X	X	X				X	X	X	X	X	X	X	X	X	
	Self-levelling Planer, 100 cm	6726632				X	X	X								X	X	X	X	X	
	Self-levelling Planer, 100 cm with 60 (fixed) / 40 (removable) drum	1111142				X	X	X								X	X	X	X	X	
	Self-levelling Planer 120 cm	7331125				X	X	X								X	X	X	X	X	
②	Note: 7-Pin Attachment Control Kit is installed as standard on High Flow (H) machines.																				
	7-Pin Attachment Control Kit **	7229102		X							X										
	7-Pin Attachment Control Kit **	7128426			X	X	X	X				X	X	X	X	X	X	X	X	X	

**HIGH FLOW
MACHINES
ONLY!**

