

Flowaid FT

Reduce water content substantially whilst retaining workability



Super plasticiser/water reducing admixture for use in GRC production

Uses

Flowaid FT enables large water reductions to be made whilst retaining workability. It's particularly suitable for the production of ready-mixed concrete and applications that require high-quality concrete and improved consistent retention.

Product Information

Product Type:	Polycarboxylic Polymer/ Lignosulphonate
Appearance:	Brown Liquid
Specific Gravity:	1.05
Chloride Content (% w/w):	<0.10% Chloride-Free
Effect on Setting:	Little Effect
Freezing Point (°C):	+1°C
Suitability:	All Portland Cements
Dosage:	0.5 - 1.5% by weight of cement (<i>confirm after trials</i>)
Storage & Shelf Life:	Min. 1 year in sealed containers stored in dry warehouse conditions (5 - 30°C) - <i>protect from frost</i>

Advantages

- Improved durability
- No retardation
- Up to 20% water reduction possible
- Can be used with acrylic polymer

Available in 5L, 25L, 200L, 1000L IBCs
Supplied by Fibre Technologies International

Technical Support

Fibre Technologies International Ltd
Avonmouth Way
Avonmouth
Bristol BS11 9YA
United Kingdom

- Tel: +44 (0) 117 982 5855
- Fax: +44 (0) 117 982 0060
- info@fibretch.org
- www.fibretch.org

